



The Wyeth-Scott Co.



Manufacturer of The More Power Puller®

Phone: 800/743-4521 or 740/345-4528 • Email: sales@wyeth-scott.com • Hours: Mon. - Fri. 8:30 – 5:00 ET

For Optimal/Safe Performance, Follow All Enclosed Instructions

ALWAYS USE THE SAFETY HANDLE INCLUDED WITH YOUR PULLER

This Puller ABSOLUTELY MUST Be Kept Greased!

Where to grease the puller:

*** 9/64" grease holes are drilled in important places of the puller for your convenience.**

- ✓ P16 = Where yoke attaches to the **frame**. Holes drilled on both arms of yoke.
- ✓ P8 = Tubular Rivet is greased from a hole drilled in the center of the R17 Reel hub.
- ✓ P9 = Rivets that attach the pawls should be greased from the underside.
- ✓ P15 = Clevis Pin found in the center of the sheave of the tackle block hook.
- ✓ SLT = All safety latch springs and screws. (puller option)

* Older Pullers > If it does not have grease holes drilled, you will need to grease around these same areas.

We recommend the use of a grease gun with small tip. If a grease gun is not available, the use of lithium grease in an aerosol can with a straw may be substituted.

- Detailed picture of labeled parts can be found in the instruction/warranty brochure •